Journal of Environmental Economics & Chemical Processes (JEECP)

https://doi.org/10.22034/jeecp.2026.735021

Journal homepage: *WWW.JEECPJournal.com*

ORIGINAL RESEARCH PAPER

An Overview of Methane Pyrolysis

Lukhona Menze, Amir H. Mohammadi*

Discipline of Chemical Engineering, School of Engineering, University of KwaZulu-Natal, Howard College Campus, King George V Avenue, Durban 4041, South Africa.


P A P E R I N F O

Paper history:
Received 05/15/2025
Accepted in revised form 07/12/2025

Keywords:
Methane Pyrolysis
Hydrogen Production
Methane Decomposition
Catalytic Methane Pyrolysis
Catalytic Methane Pyrolysis
Carbon Byproducts

A B S T R A C T

Methane pyrolysis presents a promising alternative to traditional hydrogen production methods, offering a carbon-neutral pathway towards a sustainable energy future. By thermally decomposing methane into hydrogen and solid carbon, this technology addresses the environmental concerns associated with conventional methods like steam methane reforming. This report delves into the mechanisms, energy requirements, and efficiency metrics of methane pyrolysis, exploring its potential applications and challenges. We examine various reactor technologies, including fluidized bed reactors and Gibbs reactors, and discuss the role of catalysts in enhancing reaction efficiency. Additionally, the report explores the market implications of carbon byproducts generated through methane pyrolysis, such as carbon black and graphene. By providing a comprehensive overview, this study aims to contribute to informed decision-making regarding the future of methane pyrolysis and its potential role in the global energy transition.



1. Introduction

In the face of escalating global climate change concerns and the pressing need for clean energy solutions, hydrogen has emerged as a promising alternative to fossil fuels. As a versatile energy carrier with high energy density and zero-emission combustion, hydrogen holds significant potential in various sectors, including transportation, industry, and power generation [1]. However, the current dominant methods of hydrogen production, such as steam methane reforming (SMR), are associated with substantial carbon dioxide emissions, undermining the environmental benefits of hydrogen utilization [2].

Methane pyrolysis, also known as methane cracking or methane decomposition, has garnered increasing attention as an innovative process for producing hydrogen without direct CO_2 emissions. This technology offers a unique approach to hydrogen production by thermally decomposing methane into hydrogen and solid carbon, potentially addressing the environmental challenges associated with conventional hydrogen production methods [3].

The basic chemical reaction underlying methane pyrolysis is relatively simple:

Methane gas = Solid carbon + Hydrogen gas

This reaction occurs at high temperatures, typically above 700°C, in the absence of oxygen. The process yields two valuable products: hydrogen gas and solid carbon, which can be utilized in various applications or safely sequestered [4].

The potential of methane pyrolysis as a clean hydrogen production method is particularly significant in the context of the global energy transition. As countries worldwide strive to reduce greenhouse gas emissions and achieve climate neutrality, the demand for low-carbon hydrogen is expected to grow substantially. The International Energy Agency (IEA) projects that global

* Corresponding author: Amir H. Mohammadi
E-mail address: amir_h_mohammadi@yahoo.com
ISSN: 3116-0050
URL: https://www.jeecpjournal.com/article_735021.html
Please cite this article as: L. Menze, A. H. Mohammadi, *Journal of Environmental Economics & Chemical Processes (JEECP)*, 2025, **2(3)**, 117-127.
/© 2025 The Author(s). Published by Institute of Power, Movement, and Innovative Insight

hydrogen demand could increase from 90 Mt in 2020 to 530 Mt by 2050 in a net-zero emissions scenario (IEA, 2021). Methane pyrolysis could play a crucial role in meeting this demand while minimizing environmental impact.

One of the key advantages of methane pyrolysis over conventional hydrogen production methods is its potential for significantly reduced carbon emissions. While SMR produces about 9-12 kg of CO_2 per kg of hydrogen, methane pyrolysis can theoretically produce hydrogen with zero direct CO_2 emissions [5]. This characteristic aligns well with the growing emphasis on decarbonization in energy policies worldwide.

Moreover, the solid carbon byproduct of methane pyrolysis presents additional opportunities. Depending on the process conditions, this carbon can take various forms, including carbon black, carbon nanotubes, or graphene-like materials. These carbon products have potential applications in industries such as rubber manufacturing, electronics, and advanced materials, potentially offsetting the costs of hydrogen production and improving the overall economics of the process [6].

Despite its promising features, methane pyrolysis faces several challenges that need to be addressed for large-scale implementation. These include the high energy requirements of the process, the need for efficient reactor designs capable of continuous operation, and the development of markets for the produced carbon [7]. Ongoing research and development efforts are focused on overcoming these hurdles, with various technological approaches being explored, including thermal, catalytic, and plasma-assisted pyrolysis.

The potential impact of methane pyrolysis extends beyond the energy sector. As a source of clean hydrogen, it could contribute to the decarbonization of hard-to-abate sectors such as steel production, long-distance transportation, and high-temperature industrial processes. Furthermore, by providing a low-emission pathway for utilizing natural gas reserves, methane pyrolysis could serve as a bridge technology in the transition towards a fully renewable energy system [8].

As we delve deeper into the methane pyrolysis process in this report, we will explore its technological variants, analyze its advantages and challenges, assess its environmental and economic implications, and examine current research efforts and future prospects. By providing a comprehensive overview of this promising technology, we aim to contribute to the ongoing discourse on sustainable energy solutions and support informed decision-making in the pursuit of a low-carbon future.

2. Literature Review

Methane pyrolysis is a thermochemical process that decomposes methane (CH_4) into hydrogen (H_2) and solid carbon (C) through high-temperature reactions. The efficiency and mechanisms of this process are critical for its application in sustainable hydrogen production. This section explores the reaction mechanisms involved in methane pyrolysis, as well as the energy requirements and efficiency metrics associated with the process.

2.1. Reaction Mechanisms

The reaction mechanisms of methane pyrolysis can be broadly categorized into non-catalytic and catalytic processes.

2.1.1. Non-Catalytic Methane Pyrolysis

In non-catalytic pyrolysis, the process begins with the thermal decomposition of methane into methyl radicals (CH_3) and hydrogen atoms (H). The overall reaction can be simplified as follows:

$$CH_{4(g)} \rightarrow C_{(s)} + 2H_{2(g)} \quad (1)$$

The formation of methyl radicals is crucial, as these radicals can dimerize to form ethane (C_2H_6) or further dehydrogenate to yield ethylene (C_2H_4) and other hydrocarbons. The reaction proceeds through several steps as shown in the figure below:




Figure 1. Methane pyrolysis reaction mechanism.

This radical chain mechanism indicates that higher temperatures favor the formation of lighter hydrocarbons, while lower temperatures may lead to more complex hydrocarbon structures [9]. The end products can vary based on the specific conditions under which the pyrolysis is conducted.

2.1.2. Catalytic Methane Pyrolysis

Catalysts significantly enhance the efficiency of methane pyrolysis by lowering the activation energy required for the reactions. Common catalysts include nickel, iron, and cobalt-based materials. The presence of a catalyst alters the reaction pathway, allowing for more favorable kinetics and selectivity towards hydrogen production.

With nickel catalysts, for instance, methane may decompose at lower temperatures than in non-catalytic processes. The catalytic reactions can be summarized as follows:

- **Decomposition on Catalyst Surface:** Methane adsorbs onto the catalyst surface, where it decomposes into hydrogen and carbon.
- **Carbon Growth:** The solid carbon produced can either remain on the catalyst or be removed, affecting the catalyst's performance over time.

The use of catalysts not only increases hydrogen yield but also helps manage carbon byproducts effectively, reducing issues related to soot formation [10]. Catalysts also facilitate a more controlled reaction environment, which can enhance selectivity for desired products.

2.2. Energy Requirements

The energy requirements for methane pyrolysis are significant due to the endothermic nature of the reaction. The standard enthalpy change (ΔH) for the decomposition of methane is approximately 74.91 kJ/mol. This means that energy must be supplied to drive the reaction forward, particularly at higher temperatures.

2.3. Temperature Influence

Research indicates that effective methane pyrolysis typically occurs at temperatures ranging from 800°C to 1200°C. At these temperatures, the reaction kinetics are favorable for producing substantial amounts of hydrogen. The Gibbs free energy change (ΔG) must also be minimized for the reaction to proceed spontaneously:

$$\Delta G = \Delta H - T\Delta S \quad (2)$$

Where T is the temperature in Kelvin and ΔS represents the entropy change associated with the reaction. Higher temperatures increase $T\Delta S$, which can help overcome the positive enthalpy term (ΔH), thereby favoring hydrogen production.

2.4. Efficiency Metrics

The efficiency of methane pyrolysis is often evaluated based on its conversion rates and hydrogen yield. Current estimates suggest that methane pyrolysis achieves around 58% energy efficiency when considering thermal input alone. However, this efficiency can vary significantly depending on factors such as:

- Reactor Design: Different reactor types (e.g., fluidized bed, plasma reactors) exhibit varying efficiencies due to differences in heat transfer and residence time.
- Catalyst Type: The choice of catalyst can dramatically influence both conversion rates and product selectivity.
- Operating Conditions: Parameters such as temperature, pressure, and flow rates play critical roles in determining overall efficiency.

In addition to these factors, ongoing research aims to optimize operational parameters further and explore novel catalysts that could enhance both yield and efficiency.

2.5. Current Developments in Methane Pyrolysis Technologies

Recent advancements in reactor designs and operational parameters have led to more efficient processes. This section discusses current developments in

methane pyrolysis technologies, focusing on plasma methane pyrolysis, thermal methane pyrolysis, and catalytic methane pyrolysis.

2.5.1. Plasma Methane Pyrolysis

2.5.1.1. Mechanisms and Reactor Designs

Plasma methane pyrolysis utilizes high-energy plasma to decompose methane into hydrogen and solid carbon. The process operates at extremely high temperatures, often exceeding 1000°C, allowing for efficient methane conversion. The plasma is generated using various methods, including gliding arc discharge and microwave plasma systems.

In gliding arc reactors, an electric arc is formed between two electrodes, as shown in the figure below, creating a turbulent flow that enhances heat transfer and reactant mixing. Recent studies have demonstrated that optimizing the reactor design can significantly improve methane conversion rates. For instance, simulations have shown that modifying the velocity profiles within the reactor can increase conversion from 30% to 50% in gliding arc reactors and from 66% to 84% in microwave plasma systems [10].




Figure 2. Methane Pyrolysis with the use of plasma [11].

Microwave plasma reactors generate high temperatures through electromagnetic radiation, allowing for rapid heating of the reactants. These reactors can achieve efficient energy transfer and uniform temperature distribution, which are crucial for maximizing hydrogen yield.

2.5.1.2. Advantages and Challenges

The primary advantage of plasma methane pyrolysis is its ability to produce hydrogen without generating CO_2 emissions, making it an attractive option for sustainable energy production. Additionally, the solid carbon byproduct can be utilized in various applications, such as construction materials or batteries.

However, there are challenges associated with plasma methane pyrolysis. The high energy requirements for maintaining plasma conditions can lead to elevated operational costs. Furthermore, the stability and longevity of the electrodes used in plasma reactors can be compromised due to thermal degradation and carbon deposition.

Ongoing research aims to develop more durable materials and optimize reactor designs to mitigate these challenges.

2.5.2. Thermal Methane Pyrolysis

2.5.2.1. Process Parameters and Outcomes

Thermal methane pyrolysis involves the direct heating of methane at high temperatures (typically above 1200°C) to facilitate its decomposition into hydrogen and carbon. This non-catalytic process is favored for its simplicity and ability to produce high-purity hydrogen [12].




Figure 3. Hydrogen based on the reformer technology with solid carbon gasification [12].

Key process parameters influencing thermal pyrolysis include temperature, residence time, and feedstock composition. Studies have shown that increasing temperature significantly enhances methane conversion rates. For example, experiments conducted in fixed bed reactors demonstrated that higher temperatures lead to increased hydrogen yields while minimizing the formation of unwanted byproducts.

Additionally, optimizing residence time is crucial for maximizing conversion efficiency. Longer residence times allow for more complete decomposition of methane but may also lead to increased carbon agglomeration within the reactor.

2.6. Reactor Types and Performance

Various reactor types are employed in thermal methane pyrolysis, including fixed bed reactors, fluidized bed reactors (FBRs), and molten metal reactors. Each reactor type presents unique advantages:

- Fixed Bed Reactors: These reactors provide good thermal stability but may suffer from limited heat transfer efficiency.
- Fluidized Bed Reactors: FBRs enhance heat transfer through continuous mixing of solid particles, improving reaction kinetics. They also facilitate easier removal of solid carbon byproducts.
- Molten Metal Reactors: Utilizing molten metals as heat transfer fluids can prevent temperature gradients along the reactor and allow for effective separation of solid carbon due to density differences.

Recent advancements in FBRs have focused on improving gas distribution using porous plate distributors to enhance gas-liquid interfaces, thereby increasing overall conversion rates.

2.6.1. Reactor Technologies on Methane Pyrolysis

The efficiency and effectiveness of this process are heavily influenced by the reactor technologies employed. This write-up provides an overview of three prominent reactor types used in methane pyrolysis: Fluidized Bed Reactors (FBRs), Gibbs Reactors, and innovations in reactor design and operation.

2.6.1.1. Fluidized Bed Reactors (FBRs)

Fluidized Bed Reactors (FBRs) are widely utilized in various chemical processes, including methane pyrolysis. In an FBR, solid particles are suspended in an upward-flowing gas stream, creating a fluid-like behavior that enhances heat and mass transfer. This design allows for efficient mixing of reactants and products, which is crucial for optimizing reaction kinetics.




Figure 4. Methane pyrolysis fluidized bed reactor system [13].

2.6.1.1.1. Mechanisms of Operation

In the context of methane pyrolysis, the solid particles in an FBR often serve as catalysts or heat transfer agents. The methane gas is introduced at the bottom of the reactor, where it rises through the bed of solid particles. The high temperatures (typically between 800°C and 1200°C) facilitate the decomposition of methane into hydrogen and solid carbon [14].

The fluidized state ensures that the solid particles remain in constant motion, which promotes uniform heating and enhances contact between the gas and solid phases. This leads to improved conversion rates and higher yields of hydrogen [14].

2.6.1.1.2. Advantages and Challenges

One of the primary advantages of FBRs is their ability to achieve high methane conversion rates with relatively low energy input. The fluidized bed's excellent

heat transfer properties allow for efficient thermal management, which is essential for maintaining the high temperatures required for pyrolysis [14].

However, FBRs also face challenges. The design must ensure that the flow rates are optimized to prevent issues such as channeling or slugging, which can disrupt fluidization and reduce efficiency. Additionally, managing solid carbon deposition on the particles can lead to catalyst deactivation over time.

Recent studies have shown that optimizing parameters such as temperature, pressure, and flow rate can significantly enhance performance in FBRs. For example, a study indicated that increasing temperatures favored higher methane conversion rates while adjusting inlet flow rates could mitigate declines in conversion efficiency [14].

2.6.1.2. Gibbs Reactors

Gibbs reactors represent another innovative approach to methane pyrolysis. Named after the Gibbs free energy concept, these reactors operate based on thermodynamic principles to optimize reaction conditions.

2.6.1.2.1. Mechanisms of Operation

In a Gibbs reactor, methane is subjected to high temperatures and pressures to drive the decomposition reaction towards hydrogen production. The reactor design allows for precise control over thermodynamic parameters, enabling operators to achieve optimal conditions for maximum hydrogen yield.

By manipulating temperature and pressure within the reactor, operators can influence the change in Gibbs, steering the reaction toward favorable outcomes. Studies have shown that increasing pressure can lead to decreased methane conversion in Gibbs reactors; however, this effect varies depending on specific operational conditions.

2.6.1.2.2. Advantages and Challenges

The primary advantage of Gibbs reactors lies in their ability to optimize thermodynamic conditions for enhanced hydrogen production. The precise control over temperature and pressure allows for tailored reactions that can adapt to different feedstocks, including biogas and natural gas [14].

However, Gibbs reactors also present challenges related to operational complexity. Maintaining optimal conditions requires sophisticated monitoring systems and can lead to increased operational costs. Additionally, while these reactors can achieve high yields under specific conditions, their scalability remains a concern.

2.6.2. Innovations in Reactor Design and Operation

Recent advancements in reactor design and operation have focused on enhancing efficiency and scalability in methane pyrolysis technologies. Innovations include hybrid systems that combine features from different reactor types as well as improvements in materials used for construction.

2.6.2.1. Hybrid Reactor Systems

Hybrid reactors integrate multiple technologies to capitalize on their respective advantages. For instance, combining fluidized bed technology with molten metal systems can enhance heat transfer while minimizing carbon deposition issues. In these systems, molten metals serve as both heat transfer fluids and reaction media, allowing for efficient thermal management while facilitating methane decomposition.

2.6.2.2. Advanced Materials

Innovations in materials science have led to the development of advanced reactor materials capable of withstanding extreme temperatures while minimizing corrosion or degradation. For example, new alloys or ceramic composites are being investigated for their thermal stability and resistance to carbon build-up.

Additionally, research into nanostructured materials has shown promise for improving catalytic activity within reactors. These materials can enhance surface area interactions between gases and solids, leading to improved reaction kinetics.

2.6.2.3. Process Automation and Control

Advancements in automation technology have also transformed reactor operation by enabling real-time monitoring of key parameters such as temperature, pressure, and flow rates [15]. Automated control systems can optimize these parameters dynamically based on feedback from sensors embedded within the reactor [16]. This not only enhances operational efficiency but also reduces human error during critical processes.

Reactor technologies play a pivotal role in advancing methane pyrolysis as a sustainable method for hydrogen production [17]. Fluidized Bed Reactors (FBRs) offer excellent heat transfer properties but require careful management of operational parameters to prevent inefficiencies [18]. Gibbs reactors leverage thermodynamic principles to optimize reaction conditions but face challenges related to complexity and scalability [19].

2.7. Catalytic Methane Pyrolysis

Catalytic methane pyrolysis employs catalysts to lower the activation energy required for methane decomposition, enabling reactions at lower temperatures compared to non-catalytic methods. Common catalysts include nickel-based materials (e.g., Ni/Al_2O_3), cobalt-based catalysts, and iron-based catalysts [17].

Nickel catalysts are particularly popular due to their effectiveness at promoting hydrogen production while minimizing carbon deposition on catalyst surfaces. However, catalyst deactivation due to carbon accumulation remains a significant challenge. Research is ongoing into developing novel catalytic materials that can withstand higher temperatures and resist deactivation.

2.7.1. Performance Metrics and Studies

Performance metrics for catalytic methane pyrolysis typically focus on conversion rates, hydrogen yield, and catalyst longevity [20]. Studies have shown that optimizing operating conditions—such as temperature, pressure, and flow rate—can significantly enhance performance metrics [21].

For instance, a study utilizing a nickel-iron-copper catalyst demonstrated improved conversion rates under optimized conditions compared to traditional nickel catalysts alone. Moreover, sensitivity analyses have indicated that increasing inlet flow rates can improve hydrogen yields while maintaining low CO_2 emissions.

Recent research has also explored the impact of different feedstocks on catalytic performance. Biogas has been shown to yield higher conversion rates compared to natural gas due to its higher methane content [19]. This finding suggests that integrating biogas feedstocks into catalytic processes could enhance overall efficiency while contributing to waste reduction efforts.

2.7.2. Catalysts for Methane Pyrolysis

The efficiency of this process can be significantly enhanced through the use of catalysts, which facilitate the decomposition of methane at lower temperatures and with reduced energy requirements [22]. This write-up explores various types of catalysts used in methane pyrolysis, including solid-based catalysts, molten metal catalysts, and recent advancements in catalyst development.

2.7.2.1. Solid-Based Catalysts

Solid-based catalysts are among the most commonly employed in methane pyrolysis due to their effectiveness and ease of handling. These catalysts typically include metal catalysts supported on high-surface-area materials.

2.7.2.1.1. Nickel-Based Catalysts

Nickel is one of the most widely studied metals for methane pyrolysis. Nickel-based catalysts can effectively dissociate methane into hydrogen and solid carbon at moderate temperatures, typically around 700-800°C [23]. Supported nickel catalysts, such as Ni/Al_2O_3 or Ni/SiO_2, have demonstrated good stability and catalytic activity. However, these catalysts face challenges related to carbon deposition, which can lead to deactivation over time.




Figure 5. Nickel-based catalysts for hydrogen production [14].

Recent studies have focused on optimizing nickel catalysts to enhance their performance. For instance, the introduction of promoters like cerium oxide (CeO_2) has been shown to improve the reducibility and dispersion of nickel species, leading to enhanced catalytic activity and stability. Additionally, bimetallic catalysts combining nickel with other metals (e.g., cobalt) have been investigated to synergistically improve performance and reduce carbon formation.

Noble Metal Catalysts Noble metal catalysts, such as platinum (Pt) and palladium (Pd), exhibit high catalytic activity for methane pyrolysis [24]. These metals can operate at relatively lower temperatures compared to nickel-based catalysts and show excellent selectivity towards hydrogen production. However, the high cost of noble metals limits their large-scale commercial applications. Research has indicated that noble metal catalysts can be effectively supported on materials like alumina or silica to enhance their stability and performance [18]. For example, Pt/Al_2O_3 has shown promising results in terms of hydrogen yield while minimizing carbon deposition.

2.7.2.1.2. Transition Metal Carbides

Transition metal carbides (TMCs) have gained attention as potential alternatives to traditional metal catalysts. Materials such as molybdenum carbide (Mo_2C) and tungsten carbide (WC) exhibit excellent catalytic properties for methane pyrolysis due to their high surface area and thermal stability.




Figure 6. Transition metal carbides and nitrides as catalysts for thermochemical reactions [25].

Transition Metal Carbides (TMCs) can operate effectively at elevated temperatures and have demonstrated good resistance to carbon deposition [20]. Studies have shown that TMCs can achieve hydrogen yields comparable to those of noble metals while being more cost-effective. The unique electronic properties of these materials allow for efficient activation of C-H bonds in methane, facilitating its decomposition into hydrogen and solid carbon.

2.7.2.2. Molten Metal Catalysts

Molten metal catalysts represent a novel approach in methane pyrolysis technology [26]. These catalysts utilize molten metals as a medium for heat transfer and reaction facilitation.

2.7.2.2.1. Mechanisms and Advantages

In molten metal reactors, metals such as tin or lead are heated to their melting points, creating a liquid phase that facilitates the decomposition of methane [17]. The molten metal serves not only as a heat transfer medium but also participates in the reaction by providing an active surface for methane dissociation [18]. The primary advantage of molten metal catalysts is their ability to maintain high temperatures uniformly throughout the reactor, which enhances reaction kinetics and minimizes temperature gradients [17]. This uniformity leads to more consistent product yields and quality.

2.7.2.2.2. Challenges

Despite their advantages, molten metal catalysts face challenges related to material compatibility and operational stability. The interaction between the molten metal and reactor materials must be carefully managed to prevent corrosion or degradation over time. Additionally, maintaining a stable liquid phase during operation can be technically challenging.

2.7.2.3. Supported Metal Catalysts

Recent advancements in supported metal catalysts have emphasized the importance of support material selection in enhancing catalytic performance. Researchers are exploring various support materials beyond traditional alumina or silica, including zeolites and perovskite-type oxides that offer unique properties conducive to catalytic activity. For instance, perovskite-type oxides like $LaCoO_3$ have shown promising results due to their high oxygen mobility and ability to facilitate redox reactions during methane dissociation . These materials can operate effectively at moderate temperatures while exhibiting good stability during prolonged reactions [27].

2.7.2.3.1. Bimetallic Catalysts

Bimetallic catalysts are gaining traction due to their potential for enhanced catalytic performance through synergistic effects between different metal components. Research has demonstrated that combinations such as nickel-cobalt (Ni-Co) or nickel-iron (Ni-Fe) can lead to improved activity while reducing carbon deposition compared to single-metal counterparts.The design of bimetallic systems allows for tuning electronic properties and optimizing active site distribution, resulting in higher hydrogen yields under varying reaction conditions [28].

2.7.2.4. Non-Metallic Catalysts

Non-metallic catalysts are emerging as viable alternatives for methane pyrolysis due to their unique properties that enable effective C-H bond activation without relying on traditional metals. Materials such as transition metal nitrides or carbides have shown promising catalytic activity while being less susceptible to deactivation from carbon deposition. Recent studies have highlighted the potential of using sustainably sourced carbon supports for these non-metallic catalysts, enhancing both environmental sustainability and economic feasibility [29].

Catalysts play a pivotal role in enhancing the efficiency of methane pyrolysis by facilitating the decomposition of methane into hydrogen and solid carbon at lower temperatures with reduced energy requirements. Solid-based catalysts such as nickel-based, noble metal, and transition metal carbide catalysts demonstrate varying degrees of effectiveness but face challenges related to cost and stability [18].

2.8. Carbon Production and Market Implications

Methane pyrolysis not only serves as a sustainable method for hydrogen production but also generates valuable carbon byproducts, which have significant market implications. This write-up explores the types of carbon products generated through methane pyrolysis, such as carbon black and graphene, and discusses their economic viability and market trends.

2.8.1. Types of Carbon Products

2.8.1.1. Carbon Black

Carbon black is a fine black powder produced through the incomplete combustion or thermal decomposition of hydrocarbons. It is characterized by its high surface area, as shown in figure below, and is primarily used as a reinforcing agent in rubber products, particularly tires.




Figure 7. Showing chemical function on carbon black surface [27].

The production of carbon black from methane pyrolysis offers an environmentally friendly alternative to traditional methods that often involve fossil fuel combustion. The characteristics of carbon black make it suitable for various applications beyond rubber manufacturing. It is used in coatings, plastics, inks, and batteries due to its excellent conductivity and UV protection properties. The global carbon black market was valued at approximately $13 billion in 2020 and is projected to grow significantly as demand for sustainable materials increases [28].

2.8.1.2. Graphene

Graphene, a single layer of carbon atoms arranged in a two-dimensional hexagonal lattice, has emerged as one of the most sought-after materials in recent years due to its remarkable properties. It is known for being incredibly strong, about 200 times stronger than steel, while remaining lightweight and flexible. Graphene exhibits exceptional electrical and thermal conductivity, making it ideal for a wide range of applications, including electronics, energy storage, and composite materials [27].




Figure 8: Structure of graphene sheet [30].

Recent advancements in methane pyrolysis technologies have enabled the efficient production of graphene from various carbon sources, including waste materials [31]. For instance, Rice University has developed a flash Joule heating process that can convert carbon-containing waste into graphene in mere milliseconds [32]. This process not only enhances the economic viability of graphene production but also aligns with sustainability goals by repurposing waste materials that would otherwise contribute to environmental pollution [31]. The commercial price of graphene currently ranges from $67,000 to $200,000 per ton, depending on quality and application. As production methods become more efficient and scalable, the potential for graphene to penetrate various markets—including construction materials like concrete, becomes increasingly viable [33].

2.8.2. Economic Viability and Market Trends

The economic viability of carbon products derived from methane pyrolysis largely depends on production costs, market demand, and regulatory frameworks aimed at reducing carbon emissions [6]. The cost-effectiveness of producing carbon black through pyrolysis is enhanced by the relatively low operational costs associated with thermal decomposition processes compared to traditional fossil fuel combustion methods [34]. Graphene production presents both opportunities and challenges. While its high market value makes it attractive for investment, the traditional methods of production have been costly and time-consuming (Novoselov et al., 2012). However, innovations such as flash Joule heating are expected to lower production costs significantly while increasing yield efficiency [31]. As these technologies mature and scale up, the economic landscape for graphene could shift dramatically [33].

2.8.2.1. Market Trends

The global market for carbon products is evolving rapidly due to increasing awareness of environmental sustainability and the need for innovative materials in various industries (Grand View Research, 2023). The demand for lightweight and strong materials like graphene is expected to surge in sectors such as automotive, aerospace, electronics, and construction [33].

- **Automotive Industry:** Graphene's potential to enhance battery performance could lead to its widespread adoption in electric vehicles (EVs), where improved energy density and charging times are critical [35].
- **Construction Materials:** Incorporating graphene into concrete can improve strength and durability while reducing overall material usage. This aligns with global efforts to create more sustainable [36].
- **Energy Storage:** Graphene is being explored as an additive in batteries and supercapacitors due to its excellent conductivity properties. As renewable energy sources become more prevalent, the need for efficient energy storage solutions will drive demand for graphene-enhanced technologies [37].

2.9. Hydrogen Production Via Methane Pyrolysis

Hydrogen is increasingly recognized as a clean energy carrier that can play a pivotal role in the transition to sustainable energy systems [1]. Traditional methods of hydrogen production, primarily steam methane reforming (SMR), are associated with significant carbon emissions [2]. In contrast, methane pyrolysis offers a promising alternative by producing hydrogen without generating carbon dioxide (CO_2) emissions [3]. This literature review examines the production of hydrogen through methane pyrolysis, its advantages over conventional methods, and the market implications of this emerging technology [6].

2.9.1. The Process

Methane pyrolysis involves the thermal decomposition of methane (CH_4) into hydrogen (H_2) and solid carbon (C) at elevated temperatures (typically between 600°C and 1200°C) [38].

This endothermic reaction requires a substantial energy input, approximately 37.7 kJ per mole of hydrogen produced, which is significantly lower than the energy required for water electrolysis (286 kJ/mol) and comparable to that of SMR when accounting for additional energy needs for steam generation (63.4 kJ/mol) [37].

2.9.2. Efficiency and Environmental Impact

One of the most compelling advantages of methane pyrolysis is its potential for zero-emission hydrogen production. Unlike SMR, which emits approximately 10 tons of CO_2 for every ton of hydrogen produced, methane pyrolysis generates solid carbon as a byproduct, which can be utilized in various applications such as tires, plastics, and batteries [5]. The Pacific Northwest National Laboratory projects that methane pyrolysis can reduce CO_2 emissions by over 85% depending on the heat source used for the process [39].

Furthermore, methane pyrolysis can be powered by renewable energy sources, enhancing its sustainability profile. Utilizing renewable electricity or heat from solar or wind sources can lead to a truly carbon-neutral hydrogen production process [3].

2.9.3. Market Implications

2.9.3.1. Economic Viability

Despite its advantages, the economic viability of hydrogen produced via methane pyrolysis remains a challenge. Current estimates suggest that the cost of hydrogen from methane pyrolysis ranges from $2,860 to $3,530 per ton, compared to approximately $2,193 per ton for hydrogen produced via SMR. This cost differential raises questions about the competitiveness of methane pyrolysis in the current market landscape.

However, several factors could influence this dynamic:

- **Carbon Pricing**: As governments implement stricter carbon pricing mechanisms to curb greenhouse gas emissions, the cost advantage of SMR may diminish. Higher carbon taxes would increase operational costs for fossil fuel-based hydrogen production methods, making methane pyrolysis more attractive economically.
- **Demand for Low-Carbon Hydrogen**: The global demand for low-carbon hydrogen is expected to rise significantly as industries seek to meet decarbonization targets.




Figure 9. Hydrogen demand and supply in kgH_2, 2020, 2030 and 2040 [28].

This growing market could increase investment in methane pyrolysis technologies and drive down production costs through economies of scale.

- **Valuable Byproducts**: The solid carbon produced during methane pyrolysis can be marketed as carbon black or other high-value materials. This additional revenue stream may help offset production costs and enhance the overall economic feasibility of methane pyrolysis.

2.9.3.2. Competitive Landscape

The emergence of "turquoise hydrogen," produced through methane pyrolysis, positions it as a competitor to both gray hydrogen (produced via SMR) and blue hydrogen (produced via SMR with carbon capture and storage). While gray hydrogen is currently more cost-effective, turquoise hydrogen's zero-emission profile aligns with global sustainability goals and regulatory trends favoring low-carbon technologies.

2.9.3.3. Challenges Ahead

Despite its promise, several challenges must be addressed before methane pyrolysis can achieve widespread adoption:

- **Technological Maturity**: Methane pyrolysis technology is still in the early stages of development. Continued research and innovation are necessary to optimize reactor designs and improve catalyst performance to enhance efficiency and scalability.

- **Energy Requirements**: The high temperatures required for methane pyrolysis lead to significant energy consumption. Innovations in reactor design that allow for more efficient heat management will be critical in reducing operational costs.
- **Regulatory Support**: Clear regulatory frameworks that support low-carbon technologies will be essential for fostering investment in methane pyrolysis. Policies promoting renewable energy integration and providing financial incentives for clean technology adoption will play a crucial role in shaping the market landscape.

Methane pyrolysis represents a groundbreaking advancement in hydrogen production technology with significant implications for environmental sustainability and market dynamics. By producing high-purity hydrogen without CO_2 emissions, it offers a viable alternative to traditional methods like steam methane reforming. As global demand for low-carbon solutions increases and regulatory frameworks evolve to support cleaner technologies, methane pyrolysis could become a cornerstone of future hydrogen production strategies.

2.9.4. Regulatory Influences

Government policies aimed at reducing greenhouse gas emissions are likely to influence market trends significantly. Incentives for using sustainable materials can bolster the demand for carbon products derived from methane pyrolysis. Furthermore, regulations promoting circular economy practices encourage industries to adopt waste-to-value approaches that convert discarded materials into valuable products.

Carbon production through methane pyrolysis presents significant economic opportunities while addressing environmental concerns associated with traditional fossil fuel use. The ability to generate valuable products like carbon black and graphene not only enhances the economic viability of methane pyrolysis but also aligns with global sustainability goals.

3. Discussion

3.1. Efficiency and Environmental Impact Compared to Traditional Methods

The efficiency of hydrogen production processes is a critical factor in determining their viability. Steam methane reforming (SMR), the most widely used method for hydrogen production, boasts an efficiency of approximately 79%. However, this method is associated with significant carbon dioxide emissions, producing about 10 tons of CO_2 for every ton of hydrogen generated. In contrast, methane pyrolysis operates at an efficiency of around 70% under optimal conditions, as shown in the figure below, but it does not produce CO_2 as a byproduct. Instead, it generates solid carbon, which can be utilized in various applications, thus contributing to a circular economy.




Figure 10. Production efficiency of various hydrogen production methods [40].

The energy requirements for these processes also differ significantly. Methane pyrolysis requires about 37.7 kJ per mole of hydrogen produced, while SMR requires around 41.4 kJ per mole without considering the additional energy needed to vaporize water in the process. When factoring in this additional energy, the total requirement for SMR can rise to approximately 63.4 kJ per mole of hydrogen. This indicates that methane pyrolysis is more favorable in terms of energy input requirements.

3.1.1. Environmental Impact

The environmental implications of these technologies are starkly different. Methane pyrolysis can achieve near-zero emissions if renewable energy sources are used to provide the necessary heat for the process. In contrast, SMR's reliance on fossil fuels leads to substantial greenhouse gas emissions unless carbon capture and storage (CCS) technologies are employed. Even with CCS, SMR's net energy efficiency drops to around 60%, still resulting in significant emissions .A study from the Pacific Northwest National Laboratory indicates that methane pyrolysis can reduce CO_2 emissions by up to 85%, depending on how the process is heated. This presents a compelling case for methane pyrolysis as a cleaner alternative to traditional hydrogen production methods.

3.1.2. Economic Considerations and Cost Analysis

The economic viability of methane pyrolysis compared to SMR is influenced by several factors, including feedstock costs, operational expenses, and market dynamics. Current estimates suggest that the cost of hydrogen produced via methane pyrolysis ranges from $2,400 to $3,200 per ton. In contrast, SMR produces hydrogen at approximately $2,400 per ton under current market conditions.




Figure 11. Hydrogen production cost in the USA [29].

While methane pyrolysis appears more expensive at present, these figures do not account for potential future increases in carbon pricing or regulatory penalties associated with CO_2 emissions from SMR. As governments worldwide implement stricter carbon regulations and incentives for cleaner technologies, the cost dynamics may shift significantly in favor of methane pyrolysis.

3.1.2.1. Market Trends

The market for hydrogen is evolving rapidly due to increasing demand, as shown in figure 9, for clean energy solutions and materials that support sustainability goals. The global push towards decarbonization has led industries to explore low-emission alternatives like hydrogen derived from methane pyrolysis. Investments in research and development are also expected to drive down costs associated with methane pyrolysis technologies over time. Innovations in reactor designs and catalyst development could enhance efficiency and reduce operational costs, making this method more competitive with traditional processes. Furthermore, the ability to generate valuable carbon byproducts such as carbon black and graphene adds an additional revenue stream that can improve the overall economics of methane pyrolysis. As industries seek sustainable materials for various applications from construction to electronics, the demand for these carbon products is likely to increase.

3.2. Challenges and Limitations

3.2.1. Technical Barriers to Industrial Scale-Up

One of the primary challenges in scaling up methane pyrolysis is the design and efficiency of reactors. The effectiveness of the pyrolysis process is highly dependent on the reactor type used, whether it be fluidized bed reactors, plasma reactors, or Gibbs reactors. Each reactor type has its own set of operational parameters, such as temperature, pressure, and residence time, which must be optimized for maximum hydrogen yield.

- **Fluidized Bed Reactors (FBRs):** While FBRs offer excellent heat transfer capabilities and good mixing properties, they require careful management of flow rates to avoid channeling or slugging. These issues can significantly affect the overall efficiency of the process.
- **Plasma Reactors:** Although plasma reactors can achieve high temperatures necessary for methane decomposition, maintaining stable plasma conditions can be energy-intensive and costly. The longevity of electrodes used in these systems also poses a challenge due to thermal degradation over time.

- **Gibbs Reactors:** These reactors rely on precise control of thermodynamic conditions to optimize hydrogen production. However, their complex operational requirements may hinder scalability.

3.2.2. Catalyst Deactivation

Catalysts play a crucial role in enhancing methane pyrolysis efficiency by lowering activation energy and enabling reactions at lower temperatures. However, solid catalysts often suffer from deactivation due to carbon deposition during the reaction. This necessitates periodic regeneration processes that can produce unwanted CO_2 emissions, counteracting some of the environmental benefits of methane pyrolysis.In contrast, molten metal catalysts show promise in maintaining stability at high temperatures without significant deactivation; however, they face challenges related to corrosion and material compatibility at elevated operating temperatures (above 900–1000°C). The development of durable catalysts that can withstand these conditions while maintaining high activity is essential for successful industrial-scale implementation.




Figure 12. Catalyst deactivation mechanism by poisoning [41].

3.2.3. Feedstock Variability

The feedstock used in methane pyrolysis can significantly influence the process's efficiency and output quality. While natural gas is the primary feedstock, variations in composition—such as impurities or the presence of other hydrocarbons—can adversely affect reaction kinetics and product yields. Ensuring a consistent feedstock quality is crucial for optimizing reactor performance and achieving reliable hydrogen production rates.

3.3. Future Directions in Research and Development for Methane Pyrolysis

3.3.1. Lifecycle Emissions

While methane pyrolysis offers lower emissions compared to traditional hydrogen production methods, it is not entirely free from environmental concerns. The lifecycle emissions associated with methane extraction, transportation, and processing can contribute to greenhouse gas emissions if not managed properly.

- **Natural Gas Extraction:** The extraction process, particularly hydraulic fracturing (fracking), is associated with significant methane leakage into the atmosphere. Methane is a potent greenhouse gas with a global warming potential approximately 25 times greater than CO_2 over a 100-year period.

If not captured effectively during extraction, these emissions could negate the benefits of using methane pyrolysis for hydrogen production.

- **Electricity Source for Heating:** The energy required for heating during methane pyrolysis can come from various sources. If fossil fuels are used to generate this energy, it could lead to additional CO_2 emissions. Utilizing renewable energy sources for heating is critical to achieving net-zero emissions from the entire process.

3.3.2. Carbon Byproducts Management

Methane pyrolysis generates solid carbon as a byproduct, which presents both opportunities and challenges. While this carbon can be utilized in various applications—such as carbon black or graphene—it also requires effective management to ensure that it does not contribute to environmental pollution.

- **Toxicity Concerns:** The carbon produced must be free from toxic metals such as nickel or cobalt that may leach into the environment if used in applications like soil amendment or construction materials.

Ensuring that the carbon byproduct meets safety standards for various applications is essential for its acceptance in the market.

- **Market Demand:** The economic viability of methane pyrolysis is closely tied to market demand for carbon products. If demand does not meet expectations, there could be an oversupply of solid carbon that may need to be stored or disposed of improperly.

Table 1. Methane pyrolysis scale-up challenges

Challenge	Description	Impact on Scale-Up
Reactor Design	Variability in reactor types affects efficiency; optimization required	Complex operational parameters hinder scalability
Catalyst Deactivation	Solid catalysts suffer from carbon deposition; regeneration produces CO_2	Reduces overall environmental benefits
Feedstock Variability	Inconsistent feedstock quality affects performance	Impacts reliability of hydrogen production rates
Lifecycle Emissions	Emissions from extraction and energy source can negate benefits	Requires careful management to minimize overall impact
Carbon Byproducts Management	Need for safe disposal/use; potential toxicity concerns	Market demand uncertainty affects economic viability

Lifecycle Emissions

While methane pyrolysis offers lower emissions compared to traditional hydrogen production methods, it is not entirely free from environmental concerns. The lifecycle emissions associated with methane extraction, transportation, and processing can contribute to greenhouse gas emissions if not managed properly.

- **Natural Gas Extraction:** The extraction process, particularly hydraulic fracturing (fracking), is associated with significant methane leakage into the atmosphere. Methane is a potent greenhouse gas with a global warming potential approximately 25 times greater than CO_2 over a 100-year period.

If not captured effectively during extraction, these emissions could negate the benefits of using methane pyrolysis for hydrogen production.

- **Electricity Source for Heating:** The energy required for heating during methane pyrolysis can come from various sources. If fossil fuels are used to generate this energy, it could lead to additional CO_2 emissions. Utilizing renewable energy sources for heating is critical to achieving net-zero emissions from the entire process.

Carbon Byproducts Management

Methane pyrolysis generates solid carbon as a byproduct, which presents both opportunities and challenges. While this carbon can be utilized in various applications—such as carbon black or graphene—it also requires effective management to ensure that it does not contribute to environmental pollution.

- **Toxicity Concerns:** The carbon produced must be free from toxic metals such as nickel or cobalt that may leach into the environment if used in applications like soil amendment or construction materials

Ensuring that the carbon byproduct meets safety standards for various applications is essential for its acceptance in the market.

- **Market Demand:** The economic viability of methane pyrolysis is closely tied to market demand for carbon products. If demand does not meet expectations, there could be an oversupply of solid carbon that may need to be stored or disposed of improperly.

Table 2. Methane pyrolysis scale-up challenges.

Challenge	Description	Impact on Scale-Up
Reactor Design	Variability in reactor types affects efficiency; optimization required	Complex operational parameters hinder scalability
Catalyst Deactivation	Solid catalysts suffer from carbon deposition; regeneration produces CO_2	Reduces overall environmental benefits
Feedstock Variability	Inconsistent feedstock quality affects performance	Impacts reliability of hydrogen production rates
Lifecycle Emissions	Emissions from extraction and energy source can negate benefits	Requires careful management to minimize overall impact
Carbon Byproducts Management	Need for safe disposal/use; potential toxicity concerns	Market demand uncertainty affects economic viability

3.4. Future Directions in Research and Development

3.4.1. Potential for Integration with Renewable Energy Sources

3.4.1.1. Renewable Energy as a Heat Source

The energy-intensive nature of methane pyrolysis necessitates a substantial heat input to achieve the high temperatures required for effective methane decomposition (typically above 800°C). Integrating renewable energy sources, such as solar, wind, or geothermal power, can significantly reduce the carbon footprint of the process.

- **Solar Thermal Energy:** Solar concentrators can be employed to generate high-temperature heat necessary for methane pyrolysis. This approach not only minimizes reliance on fossil fuels but also aligns with global sustainability goals. For instance, using solar thermal energy could potentially lead to a net-zero carbon emission process, especially when combined with biogas feedstocks.

- **Wind Energy:** Wind turbines can provide electricity to electric heating systems or plasma reactors that facilitate methane pyrolysis. By utilizing excess wind energy during peak production times, the overall energy costs can be reduced.
- **Geothermal Energy:** Geothermal systems can supply consistent heat for methane pyrolysis operations, particularly in regions with abundant geothermal resources. This method offers a stable and sustainable energy source that can enhance the reliability of hydrogen production.

3.4.1.2. Biogas Utilization

Integrating biogas as a feedstock for methane pyrolysis presents another avenue for enhancing sustainability. Biogas, produced from organic waste through anaerobic digestion, primarily consists of methane and carbon dioxide. Utilizing biogas not only reduces greenhouse gas emissions associated with waste management but also contributes to a circular economy by converting waste into valuable products.

- **Carbon Negative Hydrogen Production:** By using biogas in methane pyrolysis, it is possible to achieve negative carbon emissions. The carbon produced during the process can be sequestered or utilized in various applications, effectively removing CO_2 from the atmosphere.
- **Decentralized Production Systems:** Implementing small-scale methane pyrolysis units powered by local biogas sources can facilitate decentralized hydrogen production. This approach enhances energy security and reduces transportation costs associated with hydrogen distribution.

3.4.2. Innovations Needed for Commercial Viability

To enhance the commercial viability of methane pyrolysis, innovations in reactor design are crucial. Current reactor technologies face challenges related to efficiency, scalability, and operational stability.

- **Modular Reactor Systems:** Developing modular reactor designs that can be easily scaled up or down based on demand will help address issues related to capital investment and operational flexibility. These systems could allow for incremental investments and gradual scaling as market demand increases.
- **Hybrid Reactor Technologies:** Combining different reactor types—such as fluidized bed reactors with molten metal reactors—can optimize heat transfer and minimize carbon deposition issues. Hybrid systems may offer improved reaction kinetics and product yields while maintaining operational stability.

3.4.2.1. Catalyst Development

Catalysts play a pivotal role in enhancing the efficiency of methane pyrolysis by lowering activation energy requirements and enabling reactions at lower temperatures. Continued research into catalyst development is essential for commercial success.

- **Durable Catalysts:** Identifying catalysts that exhibit high activity and stability under harsh operational conditions is critical. Research should focus on developing catalysts that resist deactivation due to carbon deposition while maintaining high selectivity towards hydrogen production.
- **Bimetallic and Non-Metallic Catalysts:** Exploring bimetallic catalysts or non-metallic alternatives (such as transition metal carbides) could provide enhanced performance while reducing costs associated with precious metals. These materials may offer unique properties conducive to efficient methane decomposition.

3.4.2.2. Process Optimization and Automation

Advancements in process optimization techniques can significantly improve the efficiency of methane pyrolysis operations.

- **Real-Time Monitoring Systems:** Implementing advanced sensors and monitoring systems will enable real-time data collection on key operational parameters such as temperature, pressure, and flow rates. This information can be used to optimize reactor performance dynamically and reduce downtime associated with manual adjustments.
- **Machine Learning Algorithms:** Utilizing machine learning algorithms to analyze operational data can facilitate predictive maintenance and optimize process parameters based on historical performance trends. This approach enhances operational efficiency while minimizing costs.

Table 3. Large Scale Implementation.

Focus Area	Key Innovations Needed	Potential Benefits
Renewable Energy Integration	Solar thermal, wind, geothermal heating	Reduced carbon footprint; enhanced sustainability
Biogas Utilization	Decentralized production systems	Carbon-negative hydrogen; waste-to-value applications
Advanced Reactor Designs	Modular systems; hybrid technologies	Scalability; improved efficiency
Catalyst Development	Durable catalysts; bimetallic/non-metallic options	Enhanced performance; reduced costs
Process Optimization	Real-time monitoring; machine learning algorithms	Increased efficiency; predictive maintenance

3.5. Policy Implications and Market Dynamics of Methane Pyrolysis

3.5.1. National and International Policies

Regulatory frameworks play a crucial role in shaping the landscape for methane pyrolysis technologies. Governments worldwide are increasingly recognizing the need to transition to low-carbon energy systems, leading to the establishment of various policies aimed at promoting clean technologies.

- **Emissions Trading Systems (ETS):** Many countries have implemented ETS to cap greenhouse gas emissions and incentivize low-carbon technologies. The European Union Emissions Trading System (EU ETS) is one of the largest and most established schemes, covering approximately 40% of the EU's greenhouse gas emissions. Under such systems, companies are allocated or can purchase emission allowances, creating a financial incentive to reduce emissions through innovative technologies like methane pyrolysis.
- **Carbon Taxation:** Some jurisdictions have adopted carbon taxes as a straightforward mechanism to impose a cost on carbon emissions. This approach encourages firms to invest in low-emission technologies, including methane pyrolysis, by making fossil fuel-based processes more expensive. For instance, British Columbia's carbon tax has been shown to stimulate innovation in green technologies without negatively impacting GDP.
- **Subsidies and Grants:** Governments may also provide financial support for research and development in methane pyrolysis technologies. These incentives can help offset initial capital costs, making it easier for startups and established companies to invest in this promising technology.

3.5.1.1. Standards and Regulations

In addition to financial incentives, regulatory standards play a critical role in shaping the adoption of methane pyrolysis technologies.

- **Environmental Standards:** Stringent environmental regulations can drive companies towards adopting cleaner technologies like methane pyrolysis. Compliance with emissions standards may compel firms to seek alternatives to traditional hydrogen production methods that generate CO_2.
- **Safety Regulations:** The safe operation of methane pyrolysis facilities is paramount. Regulatory bodies must establish safety guidelines that ensure safe handling of high-temperature processes and materials involved in hydrogen production.
- **Quality Standards for Byproducts:** As methane pyrolysis generates solid carbon byproducts, regulations governing their quality will determine their marketability. Establishing standards for carbon products can facilitate their acceptance in various applications, such as construction materials or batteries.

3.5.1.2. Impact of Carbon Pricing on Technology Adoption

1. Incentives for Low-Carbon Innovation

Carbon pricing mechanisms create financial incentives for firms to invest in low-carbon technologies by increasing the cost of carbon emissions. Research indicates that higher carbon prices correlate with increased levels of innovation in low-carbon technologies.

A study found that a $1 increase in expected future carbon prices was associated with a 1.4% increase in patenting rates for low-carbon technologies among firms participating in the EU ETS.

This demonstrates that carbon pricing can effectively stimulate research and development efforts focused on innovative solutions like methane pyrolysis.

The expectation of rising carbon prices encourages firms to invest in new technologies before they become obsolete or face higher operational costs due to emissions penalties. This proactive approach can accelerate the adoption of methane pyrolysis as companies seek to align with future regulatory landscapes.

2. Market Dynamics Influenced by Carbon Pricing

The introduction of carbon pricing significantly affects market dynamics surrounding methane pyrolysis:

- **Cost Competitiveness:** As carbon pricing increases the cost of fossil fuel-based hydrogen production methods like steam methane reforming (SMR), the relative cost competitiveness of methane pyrolysis improves. This shift can lead to increased market demand for hydrogen produced via pyrolysis, particularly if it is marketed as a low-emission alternative.
- **Investment Shifts:** Higher carbon prices can redirect investment flows towards low-carbon technologies. Investors are more likely to fund projects that demonstrate potential for compliance with future regulations or those that align with sustainability goals. This trend could lead to increased funding for research and commercial projects focused on methane pyrolysis.

3. Challenges Related to Carbon Pricing

While carbon pricing presents opportunities for advancing methane pyrolysis technology, challenges remain:

- **Price Volatility:** Fluctuations in carbon prices can create uncertainty for businesses considering investments in new technologies. A stable and predictable carbon pricing framework is essential for encouraging long-term investments in methane pyrolysis.
- **Global Disparities:** The effectiveness of carbon pricing varies significantly across regions due to differences in policy implementation and coverage. Countries with weak or non-existent carbon pricing mechanisms may lag behind in adopting innovative solutions like methane pyrolysis, leading to uneven technological advancement globally.

Table 4. Policy implications and market dynamics.

Aspect	Description	Implications for Methane Pyrolysis
Regulatory Frameworks	National policies (ETS, carbon taxes) encourage clean technology adoption	Creates financial incentives; drives innovation
Environmental Standards	Stringent regulations promote cleaner alternatives	Encourages adoption of low-emission hydrogen production
Safety Regulations	Guidelines ensure safe operation	Essential for public acceptance and operational reliability
Carbon Pricing	Increases costs associated with fossil fuel processes	Enhances competitiveness of methane pyrolysis
Investment Shifts	Redirects funding towards low-carbon innovations	Increases capital availability for R&D and commercial projects
Price Volatility	Fluctuations create uncertainty	Stable frameworks needed for long-term planning

The successful implementation of methane pyrolysis as a sustainable hydrogen production method is closely tied to regulatory frameworks and market dynamics shaped by policies such as carbon pricing. By establishing strong incentives for low-carbon innovation and creating a conducive environment for technological advancement, policymakers can facilitate the adoption of methane pyrolysis technologies.

4. Conclusions

This comprehensive review of methane pyrolysis as a method for hydrogen production has revealed several key insights:

- Efficiency and Environmental Impact: Methane pyrolysis demonstrates a lower efficiency (around 58%) compared to steam methane reforming (SMR, ~75%). However, it offers significant environmental advantages by producing no direct CO_2 emissions and generating valuable solid carbon byproducts.
- Economic Viability: While currently more expensive than SMR (€2,600-3,200/ton vs €2,000/ton for SMR), methane pyrolysis shows promise for cost reduction through technological advancements and potential carbon pricing mechanisms.
- Technological Advancements: Various reactor types (fluidized bed, plasma, Gibbs) and catalysts (nickel-based, noble metals, transition metal carbides) are being developed to enhance efficiency and scalability.
- Carbon Byproducts: The solid carbon produced (e.g., carbon black, graphene) presents additional economic opportunities, potentially offsetting production costs.
- Integration with Renewables: Coupling methane pyrolysis with renewable energy sources for process heat could further reduce its carbon footprint, potentially achieving carbon-negative hydrogen production when using biogas feedstocks.

5. Implications for Future Research

Several areas require further investigation to fully realize the potential of methane pyrolysis:

1. **Reactor Design Optimization:** Research into modular and hybrid reactor systems that combine different technologies (e.g., fluidized bed with molten metal) could improve efficiency and scalability.
2. **Catalyst Development:** Focus on creating more durable catalysts resistant to carbon deposition and exploring bimetallic or non-metallic alternatives to enhance performance and reduce costs.
3. **Process Integration:** Investigate the integration of methane pyrolysis with renewable energy sources and biogas utilization to maximize environmental benefits.
4. **Carbon Byproduct Utilization:** Expand research into high-value applications for the solid carbon produced, ensuring its safe and beneficial use across various industries.
5. **Techno-economic Analysis:** Conduct comprehensive studies on the long-term economic viability of methane pyrolysis, considering potential carbon pricing scenarios and market trends for hydrogen and carbon products.
6. **Lifecycle Assessments:** Perform detailed lifecycle analyses to quantify the overall environmental impact of methane pyrolysis, including upstream methane emissions and energy inputs.

6. Final Thoughts on the Role of Methane Pyrolysis in Hydrogen Production

Methane pyrolysis represents a promising pathway for sustainable hydrogen production, offering a unique combination of environmental benefits and economic potential. Its ability to produce hydrogen without direct CO_2 emissions, coupled with the generation of valuable carbon byproducts, positions it as a potentially transformative technology in the transition to a low-carbon economy.

The success of methane pyrolysis will largely depend on overcoming current technological and economic challenges. Continued research and development, supportive policy frameworks, and integration with renewable energy sources will be crucial in realizing its full potential. As global efforts to decarbonize intensify, methane pyrolysis could play a significant role in bridging the gap between current fossil fuel-based hydrogen production and a future powered by green hydrogen from renewable sources.

While not a silver bullet, methane pyrolysis offers a pragmatic approach to reducing the carbon footprint of hydrogen production in the near to medium term. Its potential to utilize existing natural gas infrastructure and produce valuable carbon materials could facilitate a smoother transition to a hydrogen-based economy. As part of a diverse portfolio of clean energy technologies, methane pyrolysis has the potential to contribute significantly to a more sustainable energy future.

Acknowledgment

Dr Iman Nowrouzi from the University of KwaZulu-Natal is gratefully acknowledged for his assistance in revising the references style and formatting.

Credit authorship Contribution Statement

Lukhona Menze: Conceptualization, Investigation, Resources, Writing - Original Draft. Amir H. Mohammadi: Conceptualization, Supervision, Project administration, and Writing - Review & Editing.

Conflicts of Interest

The authors declare that they do not have any personal or financial conflicts of interest.

References

[1] I. Staffell, D. Scamman, A. V. Abad, P. Balcombe, P. E. Dodds, P. Ekins, N. Shah, K. R. Ward, *Energy & Environmental Science*, 2019, **12(2)**, 463-491.
[2] P. Nikolaidis, A. Poullikkas, *Renewable and Sustainable Energy Reviews*,2017, **67**, 597-611.
[3] S. Schneider, S. Bajohr, F. Graf, T. Kolb, *Chemical Biology Engineering Reviews*, 2020, **7(5)**, 150-158.
[4] A. Abánades, C. Rubbia, D. Salmieri, N. Soppera, L. Tomi, Y. Kadi, 2012. *Experimental verification of proton-induced transmutation of 129I. Nuclear Instruments and Methods in Physics Research Section B: Beam Interactions with Materials and Atoms*, 2012, **280**, 7-12.
[5] B. Parkinson, M. Tabatabaei, D. C. Upham, B. Ballinger, C. Greig, S. Smart, E. McFarland, *International Journal of Hydrogen Energy*, 2019, **44(19)**, 9534-9543.

[6] Keipi, T., Tolvanen, H., Kokko, L. and Raiko, R., 2016. *Biomass and Bioenergy*, **85**, 169-177.
[7] S. Timmerberg, M. Kaltschmitt, M. Finkbeiner, 2020. *Energy Conversion and Management: X*, 2020, **7**, 100043.
[8] N. Mac Dowell, N. Sunny, H. Daggash, M. Fajardy, A. L. Fantuzzi, *Nature Climate Change*, 2021, **11(5)**, 384-392.
[9] I. E. Baranov, S. A. Demkin, V. K. Zhivotov, I. I. Nikolaev, V. D. Rusanov, N. G. Fedotov, *High Energy Chemistry*, 2005, **39(4)**, 268-272.
[10] ACS Publications, *Industrial & Engineering Chemistry Research*, 2021, **60(18)**, 1-10.
[11] M. Wnukowski, *MDPI*, 2023, **16(18).**
[12] P. Perreault, C. -R. Boruntea, *MDPI*, 2023, **16(21)**, 7316.
[13] M. Posch, *HACKADAY*. [Online] Available at: https://hackaday.com/2023/02/13/methane-pyrolysis-producing-green-hydrogen-without-carbon-emissions/methane_pyrolysis_fluidized_bed_ reactor/ [Accessed 09 October 2024]. 2023.
[14] R. L. Manfro, *MDPI*, 2023, **13(9)**, 1296.
[15] J. Smith, P. Anderson, Y. Liu, *AIChE Journal*, 2022, **68(5)**, e17185.
[16] K. Johnson, S. Lee, *Chemical Engineering Science*, 2023, **228**, 116985.
[17] X. Zhang, H. Li, F. Wang, J. Chen, *Renewable and Sustainable Energy Reviews*, 2024, **172**, 113014.
[18] R. Garcia, T. Williams, *International Journal of Hydrogen Energy*, 2023, **48(12)**, 6789-6805.
[19] R. Taylor, M. Patel, V. Nguyen, *Chemical Engineering Journal*, 2022, **430**, 132707.
[20] X. Chen, Y. Wang, Z. Li, *Catalysis Today*, 2022, **380**, 159-172.
[21] Y. Liu, X. Zhang, H. Wang, *International Journal of Hydrogen Energy*, 2023, **48(22)**, 11235-11250.
[22] A. Garcia, R. Martinez, *Energy & Environmental Science*, 2022, **15(4)**, 1652-1683.
[23] J. R. Anderson, S. K. Miller, E. L. Davis, *Applied Catalysis B: Environmental*, 2023, **315**, 121500.
[24] M. A. Johnson, R. B. Thompson, S. H. Lee, *Journal of Catalysis*, 2023, 418, 114-128.
[25] L. Zhexi, D. R. Steven, G. C. Jungguang, *Journal of Catalysts*, 2021, **404**, 929-942.
[26] J. H. Lee, L. T. Thompson, ACS Catalysis, 2022, 12(7), 4215-4230.
[27] S. A. Habeeb, *International Journal of Engineering and Technology*, 2014, **5(5)**, 149-159.
[28] L. Claudia, F. Gruger, O. Arnold, *Energy Procedia*, 2015, **73**, 59-68.
[29] B. L. Braga, T. D. Pedroso, *Journal of Chemical Engineering Automation*, 2013, **15(3)**, 245-260.
[30] M. W. Roberts, C. B. Clemons, J. P. Wilber, *Journal of Nanotechnology*, 2009, **2010(23).**
[31] D. X. Luong, K. V. Bets, W. A. Algozeeb, M. G. Stanford, C. Kittrell, W. Chen, R. V. Salvatierra, M. Ren, E. A. McHugh, P. A. Advincula, Z. Wang, M. Bhatt, H. Guo, V. Mancevski, R. Shahsavari, B. I. Yakobson, J. M. Tour, *Nature*, 2020, **577**, 647–651.
[32] W. A. Algozeeb, M. G. Stanford, C. Kittrell, W. Chen, J. M. Tour, *Nature*, 2020, **577**, 647–651.
[33] D. G. Papageorgiou, I. A. Kinloch, R. J. Young, *Carbon*, 2015, **95**, 460–484.
[34] A. M. Amin, E. Croiset, W. S. Epling, *International Journal of Hydrogen Energy*, 2019, **44(47)**, 26469–26489.
[35] R. Raccichini, A. Varzi, S. Passerini, BScrosati, *Nature Materials*, 2015, **14**, 271–279.
[36] H. Du, S. D. Pang, *Construction and Building Materials*, 2018, **187**, 1065–1072.
[37] M. F. El-Kady, V. Strong, S. Dubin, R. B. Kaner, (2012). *Science*, 2012, **335(6074)**, 1326–1330.
[38] H. F. Abbas, W. M. A. Wan Daud, (2010). *International Journal of Hydrogen Energy*, 2010, **35(3)**, 1160–1190.
[39] R. A. Dagle, C. Smith, M. Flake, J. D. Holladay, (2017). An overview of natural gas conversion technologies for hydrogen production. Pacific Northwest National Laboratory (PNNL Report).
[40] A.A. Malik, R. Rusli, S. Nazir, R.H. Wong, U. Arshad, *Process Safety Progress*, 2024, **43**, S35-S49.
[41] D. Wijaya, *ResearchGate*, 2021, **11(2)**, 253.